

# TFC-4M | M-Series (No HazMat) Fuel Trailer



This trailer features four single-wall 119-gallon stainless steel tanks. All the tanks are individually baffled and come with locking fill caps, level gauges, rollover vents, and sump valves. Individual shutoff valves allow for precise fuel control and on-road safety. The tanks are mounted on a 7K GVW dual axle trailer, which is DOT-approved and can be towed on public highways when full without needing Hazmat.

## STANDARD FEATURES

- Tank Level gauge, lockable fill cap, roll over vent
- Stainless Steel Construction, baffles to prevent fuel sloshing
- Powder coat paint with base coat primer
- Integrated fuel sump with spring close valve
- Hoses, piping and fittings are aviation grade
- Ball valve installed to isolate the tank.  
Top mounted

## SPECIFICATIONS

Tank Size	119-gallons ea. (4 tanks)
Tank Thickness	12 Gauge
DOT Status	Approved for Gas & Diesel
Axles	2 @ 3,500 lbs each
Hubs	5 x 4.5"
Tires	15" Radial
Fuel Baffles	1
Trailer Frame	4" Channel frame
GVWR	7,000 lbs
LxWxH	159" x 71.5" x 60"

We build your trailer according to your specs.  
Please contact us for any special features.

**1-800-994-TANK (8265)**



14700 Industry Circle  
La Mirada, CA 90638  
PH: 714-226-1914  
[transfueler.com](http://transfueler.com)



# TFC-4M | M-Series (No HazMat) Fuel Trailer



Our standard equipment packages are all made up of proven names such as Great Plains Industries, Facet, OPW, Continental Hose, and Hannay. We can customize the equipment packages to run off 12-volt DC, 115-volt AC, or a gasoline-powered pump.

## UPGRADES & ACCESSORIES

- TCS certifiable re-sale meters
- Lockable steel equipment cabinets
- Solar re-charge systems
- Re-Fuel / De-Fuel system
- Hose and reel sizes up to 150' long and 2" diameter

## Watch the Walkaround Video



We build your trailer according to your specs.  
Please contact us for any special features.

**1-800-994-TANK (8265)**



14700 Industry Circle  
La Mirada, CA 90638  
PH: 714-226-1914  
[transfueler.com](http://transfueler.com)

